



WAGO SUPPLY MODULE; FOR FLAT CABLE; 2-POLE; BLACK

Note on Contact Resistance: approx. 1 m² of contact resistance approx. 0.25 m² contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 50; V

Tensiune nominala de supratensiune (III/3): 0,8; kV

Curent nominal: 3; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: IDC;

Tip actionare: Operating tool;

Conductor diameter: 0,6 ... 0,8 mm;

Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;

Numar poli: 2;

Latime: 17,7 mm / 0.697 inch;

Inaltime: 23,45 mm / 0.923 inch;

Adancime: 36,8 mm / 1.449 inch;

Technologie: KNX;

Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;

Number of mating cycles: ?200;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Application: KNX;

Suitable: for flat cable 2 x 1.5 mm²;

Mismating protection: Yes;

Locking of plug-in connection: locking lever;

Culoare: black;

Material izolator: Polyamide 66 (PA 66);

Fire class per EN 50575: Eca;

Contact material: Copper or copper alloy (surface-treated);

Greutate: 16; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)

PVC flat cable for temperatures -15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;

Product Group: 20 (WINSTA);

Tip ambalare: BOX;

Tara de origine: CH;

GTIN: 4045454267391;

Customs tariff number: 85366990990;

Pret: 89,70 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/supply-module-for-flat-cable-2-pole-black-143759>