



**WAGO 8-LEVEL TERMINAL BLOCK FOR MATRIX PATCHING; FOR 35 X 7.5  
MOUNTING RAIL; 1,50 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Curent nominal: 10; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;  
Fine-stranded conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;  
Strip length: 8 ... 10 mm / 0.31 ... 0.39 inch;  
Numar total de conexiuni: 32;  
Total number of potentials: 8;  
Numar nivele: 8;  
Wiring type: Front-entry wiring;  
Latime: 7.62 mm / 0.3 inch;  
Inaltime from upper-edge of DIN-rail: 58.5 mm / 2.303 inch;  
Adancime: 226 mm / 8.898 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking: a-b-c-d-e-f-g-h--h-g-f-e-d-c-b-a;  
Marking level: Center marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 1,169; MJ  
Greutate: 72,2; g  
Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4045454187033;  
Customs tariff number: 85369010000;  
Pret: 103,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/8-level-terminal-block-for-matrix-patching-for-35-x-7-5-mounting-rail-1-50-mm2-gray-143853>