



**WAGO COMPACT SPLICING CONNECTOR; FOR ALL CONDUCTOR TYPES; FOR EX
E APPLICATIONS; MAX. 4 MM²; 5-CONDUCTOR; WITH LEVERS; TRANSPARENT
HOUSING; OPERATING TEMPERATURE (MAX.): 105 °C; 4,00 MM²; TRANSPARENT**

Ratings per: IEC/EN 60079-7;
Tensiune nominala UL (Use Group C): 440; V
Curent nominal UL (Use Group C): 20; A
Certificari: UL 60079;
Tensiune nominala EN (Ex e II): 440; V
Curent nominal (Ex e II): 32; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Lever;
Connectable conductor materials: Copper;
Nominal cross-section: 4 mm²;
Solid conductor: 0,2 ... 4 mm² / 24 ... 12 AWG;
Stranded conductor: 0,2 ... 4 mm² / 24 ... 12 AWG;
Fine-stranded conductor: 0,14 ... 4 mm² / 24 ... 12 AWG;
Strip length: 11 mm / 0.43 inch;
Numar total de conexiuni: 5;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Latime: 29,9 mm / 1.177 inch;
Inaltime: 8,3 mm / 0.327 inch;
Adancime: 18,6 mm / 0.732 inch;
Culoare: transparent;
Flammability class per UL94: V2;
Greutate: 4,4; g
Continuous operating temperature: 105 °C;
Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4055143837330;
Customs tariff number: 85369010000;
Pret: 5,67 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/compact-splicing-connector-for-all-conductor-types-for-ex-e-applications-max-4-mm2-5-conductor-with-levers-transparent-housing-operating-temperature-max-105-0c-4-00-mm2-transparent-144066>