



**WAGO COMPONENT TERMINAL BLOCK; 2-CONDUCTOR; WITH DIODE 1N5408;  
ANODE, RIGHT SIDE; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 4 MM<sup>2</sup>; PUSH-IN CAGE  
CLAMP®; 4,00 MM<sup>2</sup>; GRAY**

Tesiune nominala: 250; V

Reverse voltage: 1.000; V

Ratings per: IEC/EN 60947-7-1;

Curent nominal: 1,5; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm<sup>2</sup>;

Solid conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;

Solid conductor; push-in termination: 1,5 ... 6 mm<sup>2</sup> / 14 ... 10 AWG;

Fine-stranded conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;

Fine-stranded conductor; with insulated ferrule: 1,5 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1,5 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 6,2 mm / 0.244 inch;

Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;

Adancime: 52,3 mm / 2.059 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,142; MJ  
Greutate: 8,3; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821230953;  
Customs tariff number: 85369010000;  
Pret: 28,43 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/component-terminal-block-2-conductor-with-diode-1n5408-anode-right-side-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-push-in-cage-clamp-4-00-mm2-gray-144210>