



**WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 4 MM<sup>2</sup>; SUITABLE FOR EX E II APPLICATIONS; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 4,00 MM<sup>2</sup>; LIGHT GRAY**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala EN (Ex e II): 550; V  
Curent nominal (Ex e II): 30; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;  
Numar total de conexiuni: 3;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 6 mm / 0.236 inch;  
Inaltime from upper-edge of DIN-rail: 37 mm / 1.457 inch;  
Adancime: 61.5 mm / 2.421 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: light gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,185; MJ  
Greutate: 10,2; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4044918325400;  
Customs tariff number: 85369010000;  
Pret: 8,96 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-through-terminal-block-4-mm2-suitable-for-ex-e-ii-applications-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-4-00-mm2-light-gray-144235>