



WAGO 4-CONDUCTOR DISCONNECT/TEST TERMINAL BLOCK; WITHOUT PIVOTING KNIFE DISCONNECT; WITH TOUCH-PROOF TEST SOCKETS; TEST SOCKET, RED; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; GRAY

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 10; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper; Aluminum;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): 12 AWG: THHN, THWN;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 52,5 mm / 2.067 inch;

Adancime: 73 mm / 2.874 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Greutate: 9,3; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918691338;
Customs tariff number: 85369010000;
Pret: 20,96 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-disconnect-test-terminal-block-without-pivoting-knife-disconnect-with-touch-proof-test-sockets-test-socket-red-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-144263>