



WAGO THR MALE HEADER; 1.4 MM Ø SOLDER PIN; STRAIGHT; CLAMPING COLLAR; PIN SPACING 5 MM; 3-POLE; LIGHT GRAY

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Numar poli: 3;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 29,2 mm / 1.15 inch;

Inaltime: 21,9 mm / 0.862 inch;

Inaltime de la fata: 19,5 mm / 0.768 inch;

Adancime: 14,4 mm / 0.567 inch;

Lungimea pinului de contact: 2,4; mm

Diametrul pinului de contact: 1,4; mm

Diametru placat prin gaura (THR): 1,6 (+0,1) mm;

Tip montaj: Mounting flange;
Tip montaj: Feed-through mounting; Panel mounting;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for PCB;
Mismating protection: No;
Mating direction to the PCB: 90; °
Locking of plug-in connection: Locking latch;
PCB contact: THR;
Culoare: light gray;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,058; MJ
Greutate: 2,5; g
Temperatura lucru: -60 ... +100 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821395706;
Customs tariff number: 85366990990;
Pret: 5,79 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-straight-clamping-collar-pin-spacing-5-mm-3-pole-light-gray-144317>