



**WAGO 1-CONDUCTOR/1-PIN DOUBLE DECK RECEPTACLE TERMINAL BLOCK;
GROUND CONDUCTOR/THROUGH TERMINAL BLOCK; PE/L; WITH MARKER
CARRIER; SUITABLE FOR EX NA APPLICATIONS; FOR DIN-RAIL 35 X 15 AND 35 X
7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala de supratensiune (III/2): 6; kV

Curent nominal: 20; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala EN (Ex e II): 630; V

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2.5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0.75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2.5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2.5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 5.2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 61.4 mm / 2.417 inch;

Adancime: 80.1 mm / 3.154 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Potential marking: PE/L;
Marking level: Side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 14,9; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143299466;
Customs tariff number: 85366990990;
Pret: 28,60 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-1-pin-double-deck-receptacle-terminal-block-ground-conductor-through-terminal-block-pe-l-with-marker-carrier-suitable-for-ex-na-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-144608>