



**WAGO 2-CONDUCTOR/2-PIN, DOUBLE-DECK CARRIER TERMINAL BLOCK; 2-CONDUCTOR/2-PIN GROUND TERMINAL BLOCK; PE; INTERNAL COMMONING; SUITABLE FOR EX NA APPLICATIONS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 2,50 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2.5 mm<sup>2</sup>;

Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Solid conductor; push-in termination: 0.75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2.5 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2.5 mm<sup>2</sup> / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 5.2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 51.3 mm / 2.02 inch;

Adancime: 80.1 mm / 3.154 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Potential marking: PE;

Marking level: Side marking;  
Culoare: green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 30,4; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143257824;  
Customs tariff number: 85366990990;  
Pret: 32,61 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-2-pin-double-deck-carrier-terminal-block-2-conductor-2-pin-ground-terminal-block-pe-internal-commoning-suitable-for-ex-na-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-green-yellow-144619>