



**WAGO 4-CONDUCTOR SENSOR SUPPLY TERMINAL BLOCK; LED (GREEN); WITH GROUND CONTACT; WITH PLUGGABLE SIGNAL LEVEL; 1 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 1,00 MM<sup>2</sup>; ORANGE**

Voltage type 1: DC;

Tensiune nominala: 24; V

Curent nominal: 13,5; A

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 15; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group C): 24; V

Curent nominal CSA (Use Group C): 10; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1 mm<sup>2</sup>;

Solid conductor: 0.14 ... 1.5 mm<sup>2</sup> / 24 ... 16 AWG;

Solid conductor; push-in termination: 0.5 ... 1.5 mm<sup>2</sup> / 20 ... 16 AWG;

Fine-stranded conductor: 0.14 ... 1.5 mm<sup>2</sup> / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 0.75 mm<sup>2</sup> / 20 ... 18 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.5 ... 0.75 mm<sup>2</sup> / 20 ... 18 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar total de conexiuni: 8;

Total number of potentials: 5;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 7 mm / 0.276 inch;

Inaltime from upper-edge of DIN-rail: 52.4 mm / 2.063 inch;

Adancime: 97.3 mm / 3.831 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: orange;

Material izolator: Polyamide 66 (PA 66);

Greutate: 21,7; g

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4055143525527;

Customs tariff number: 85369010000;

Pret: 89,28 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-sensor-supply-terminal-block-led-green-with-ground-contact-with-pluggable-signal-level-1-mm2-push-in-cage-clamp-1-00-mm2-orange-144628>