



**WAGO 4-CONDUCTOR SENSOR TERMINAL BLOCK; LED (YELLOW); FOR NPN-(LOW-SIDE) SWITCHING SENSORS; WITH GROUND CONNECTION VIA PUSH-IN TYPE JUMPER BARS; 1 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 1,00 MM<sup>2</sup>; GRAY**

Voltage type 1: DC;

Tensiune nominala: 24; V

Ratings per: IEC/EN 60947-7-1;

Curent nominal: 13,5; A

Tensiune nominala UL (Use Group C): 24; V

Curent nominal UL (Use Group C): 15; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group C): 24; V

Curent nominal CSA (Use Group C): 10; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1 mm<sup>2</sup>;

Solid conductor: 0.14 ... 1.5 mm<sup>2</sup> / 24 ... 16 AWG;

Solid conductor; push-in termination: 0.5 ... 1.5 mm<sup>2</sup> / 20 ... 16 AWG;

Fine-stranded conductor: 0.14 ... 1.5 mm<sup>2</sup> / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 0.75 mm<sup>2</sup> / 20 ... 18 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.5 ... 0.75 mm<sup>2</sup> / 20 ... 18 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar total de conexiuni: 10;

Total number of potentials: 5;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 7 mm / 0.276 inch;  
Inaltime from upper-edge of DIN-rail: 52.4 mm / 2.063 inch;  
Adancime: 97.3 mm / 3.831 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 19,4; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143452885;  
Customs tariff number: 85369010000;  
Pret: 80,68 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-sensor-terminal-block-led-yellow-for-npn-low-side-switching-sensors-with-ground-connection-via-push-in-type-jumper-bars-1-mm2-push-in-cage-clamp-1-00-mm2-gray-144646>