



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 2.5 MM²; LATERAL MARKER SLOTS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 2,50 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper; Aluminum;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Note (conductor cross-section): 12 AWG: THHN, THWN;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 30,5 mm / 1.201 inch;

Adancime: 42,5 mm / 1.673 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,08; MJ

Greutate: 4,1; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: IN;

GTIN: 4045454075552;

Customs tariff number: 85369010000;

Pret: 5,55 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-2-5-mm2-lateral-marker-slots-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-2-50-mm2-gray-144669>