



**WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID AND STRANDED CONDUCTORS; MAX. 6 MM<sup>2</sup>; 3-CONDUCTOR; TRANSPARENT HOUSING; RED COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 6,00 MM<sup>2</sup>**

Ratings per: IEC/EN 60664-1;  
Tesiune nominala (II/2): 400; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 41; A  
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;  
Tehnologie conexiune: PUSH WIRE®;  
Tip actionare: Push-in;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 2,5 ... 6 mm<sup>2</sup> / 14 ... 10 AWG;  
Stranded conductor: 2,5 ... 6 mm<sup>2</sup> / 14 ... 10 AWG;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Numar total de conexiuni: 3;  
Total number of potentials: 1;  
Wiring type: Side-entry wiring;  
Latime: 25,6 mm / 1.008 inch;  
Inaltime: 14,2 mm / 0.559 inch;  
Adancime: 20,1 mm / 0.791 inch;  
Cover Culoare: red;  
Flammability class per UL94: V2;  
Fire load: 0,115; MJ  
Greutate: 5,8; g  
Surrounding air temperature (operation): 60 °C;  
Continuous operating temperature: 105 °C;  
Tip ambalare: BOX;  
Tara de origine: CN;

GTIN: 4050821215141;  
Customs tariff number: 85369010000;  
Pret: 2,57 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-and-stranded-conductors-max-6-mm2-3-conductor-transparent-housing-red-cover-surrounding-air-temperature-max-600c-6-00-mm2-144675>