



WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID CONDUCTORS; MAX. 4 MM²; 4-CONDUCTOR; BROWN CLEAR HOUSING; RED COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 2,50 MM²

Ratings per: IEC/EN 60664-1;
Tensiune nominala (II/2): 400; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 32; A
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Connectable conductor materials: Copper; Aluminum;
Strip length: 12 mm / 0.47 inch;
Numar total de conexiuni: 6;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Latime: 13 mm / 0.512 inch;
Inaltime: 13,1 mm / 0.516 inch;
Adancime: 19,5 mm / 0.768 inch;
Cover Culoare: red;
Flammability class per UL94: V2;
Greutate: 2,4; g
Surrounding air temperature (operation): 60 °C;
Continuous operating temperature: 105 °C;
Product Group: 7 (Push Wire Conn.);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4055143243681;
Customs tariff number: 85369010000;

Pret: 2,02 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-conductors-max-4-mm2-4-conductor-brown-clear-housing-red-cover-surrounding-air-temperature-max-600c-2-50-mm2-144678>