



**WAGO MICRO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID CONDUCTORS; 0.8 MM Ø; 4-CONDUCTOR; LIGHT GRAY COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; RED**

Ratings per: EN 60664;  
Tesiune nominala (II/2): 100; V  
Tensiune nominala de supratensiune (II/2): 1,5; kV  
Curent nominal: 6; A  
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;  
Tehnologie conexiune: PUSH WIRE®;  
Tip actionare: Push-in;  
Connectable conductor materials: Copper;  
Conductor diameter: 0,6 ... 0,8 mm;  
Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 10 mm / 0.394 inch;  
Inaltime: 6,8 mm / 0.268 inch;  
Adancime: 10 mm / 0.394 inch;  
Culoare: red;  
Fire load: 0,012; MJ  
Greutate: 0,8; g  
Surrounding air temperature (operation): 60 °C;  
Continuous operating temperature: 105 °C;  
Tip ambalare: BOX;  
Tara de origine: DE;

GTIN: 4044918441025;  
Customs tariff number: 85369010000;  
Pret: 1,12 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/micro-push-wire-connector-for-junction-boxes-for-solid-conductors-0-8-mm-oe-4-conductor-light-gray-cover-surrounding-air-temperature-max-600c-red-144681>