



WAGO 2-CONDUCTOR FEMALE CONNECTOR; 4 MM²; 5-POLE; 4,00 MM²; GRAY

Ratings per: IEC/EN 61984;
Tensiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 32; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Nominal cross-section: 4 mm²;
Solid conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar poli: 5;
Numar total de conexiuni: 10;
Total number of potentials: 5;
Wiring type: Front-entry wiring;
Latime: 25 mm / 0.984 inch;
Inaltime: 45,2 mm / 1.78 inch;
Adancime: 35,9 mm / 1.413 inch;
Module Latime: 5 mm / 0.197 inch;
Marking level: Side marking;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductor;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,422; MJ
Greutate: 26; g

Product Group: 18 (X-COM-System);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4044918474054;
Customs tariff number: 85366990990;
Pret: 45,86 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-female-connector-4-mm2-5-pole-4-00-mm2-gray-144721>