



WAGO MICRO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID CONDUCTORS; 0.8 MM Ø; 8-CONDUCTOR; LIGHT GRAY HOUSING; LIGHT GRAY COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; LIGHT GRAY

Ratings per: EN 60664;

Tensiune nominala (II/2): 100; V

Tensiune nominala de supratensiune (II/2): 1,5; kV

Curent nominal: 6; A

Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Push-in;

Connectable conductor materials: Copper;

Conductor diameter: 0,6 ... 0,8 mm;

Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;

Numar total de conexiuni: 8;

Total number of potentials: 1;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 18,4 mm / 0.724 inch;

Inaltime: 6,8 mm / 0.268 inch;

Adancime: 10 mm / 0.394 inch;

Culoare: light gray;

Fire load: 0,019; MJ

Greutate: 1,4; g

Surrounding air temperature (operation): 60 °C;

Continuous operating temperature: 105 °C;

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4044918502689;
Customs tariff number: 85369010000;
Pret: 1,85 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/micro-push-wire-connector-for-junction-boxes-for-solid-conductors-0-8-mm-oe-8-conductor-light-gray-housing-light-gray-cover-surrounding-air-temperature-max-600c-light-gray-144734>