



### **WAGO 2-CONDUCTOR FEMALE CONNECTOR; 4 MM<sup>2</sup>; 7-POLE; 4,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 61984;  
Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Nominal cross-section: 4 mm<sup>2</sup>;  
Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar poli: 7;  
Numar total de conexiuni: 14;  
Total number of potentials: 7;  
Wiring type: Front-entry wiring;  
Latime: 35 mm / 1.378 inch;  
Inaltime: 45,2 mm / 1.78 inch;  
Adancime: 35,9 mm / 1.413 inch;  
Module Latime: 5 mm / 0.197 inch;  
Marking level: Side marking;  
Tip contact (pluggable connector): Conector mama/priza;  
Connector (connection type): for conductor;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,592; MJ  
Greutate: 36,3; g

Product Group: 18 (X-COM-System);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918474115;  
Customs tariff number: 85366990990;  
Pret: 62,94 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-female-connector-4-mm2-7-pole-4-00-mm2-gray-144785>