



WAGO 1-CONDUCTOR FEMALE PLUG; ANGLED; 4 MM²; 12-POLE; 4,00 MM²; GRAY

Ratings per: IEC/EN 61984;
Tensiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 32; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Nominal cross-section: 4 mm²;
Solid conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar poli: 12;
Numar total de conexiuni: 12;
Total number of potentials: 12;
Wiring type: Front-entry wiring;
Latime: 60 mm / 2.362 inch;
Inaltime: 37,1 mm / 1.461 inch;
Adancime: 26,5 mm / 1.043 inch;
Module Latime: 5 mm / 0.197 inch;
Marking level: Side marking;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductor;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,527; MJ
Greutate: 29,7; g

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918547734;
Customs tariff number: 85366990990;
Pret: 53,99 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-female-plug-angled-4-mm2-12-pole-4-00-mm2-gray-145153>