



WAGO 1-CONDUCTOR FEMALE PLUG; 2.5 MM²; 3-POLE; 2,50 MM²; GRAY

Ratings per: IEC/EN 61984;

Tensiune nominala (III/3): 690; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Curent nominal 2: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2.5 mm²;

Solid conductor: 0.25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0.75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0.25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2.5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2.5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar poli: 3;

Numar total de conexiuni: 3;

Total number of potentials: 3;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 15.6 mm / 0.614 inch;

Inaltime: 40.5 mm / 1.594 inch;

Adancime: 22.4 mm / 0.882 inch;

Module Latime: 5.2 mm / 0.205 inch;

Marking level: Side marking;

Tip contact (pluggable connector): Conector mama/priza;

Connector (connection type): for conductors;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,166; MJ

Greutate: 9,8; g

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4050821242758;

Customs tariff number: 85366990990;

Pret: 14,99 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-female-plug-2-5-mm2-3-pole-2-50-mm2-gray-145158>