



**WAGO BOARD-TO-BOARD LINK; PIN SPACING 4 MM; 4-POLE; LENGTH: 28 MM;**  
**WHITE**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 63; V  
Tensiune nominala de supratensiune (III/3): 2,5; kV  
Tensiune nominala (III/2): 160; V  
Tensiune nominala de supratensiune (III/2): 2,5; kV  
Tensiune nominala (II/2): 320; V  
Tensiune nominala de supratensiune (II/2): 2,5; kV  
Curent nominal: 9; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Tensiune nominala UL 1977: 250; V  
Curent nominal UL 1977: 9; A  
Numar poli: 4;  
Total number of potentials: 4;  
Numar tipuri de conexiuni: 1;  
Distanta intre pini: 4 mm / 0.157 inch;  
Latime: 15,4 mm / 0.606 inch;  
Inaltime: 2,6 mm / 0.102 inch;  
Adancime: 28 mm / 1.102 inch;  
Mating cycles (max.): 10;  
Number of mating cycles: max. 10 connections/disconnections;  
Suitable: for SMD PCB Terminal Blocks; 2060 Series;  
Culoare: white;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;

Contact material: Copper alloy;  
Contact plating: silver-plated;  
Greutate: 0,9; g  
Temperatura lucru: -60 ... +105 °C;  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4055143303842;  
Customs tariff number: 85369010000;  
Pret: 4,90 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/board-to-board-link-pin-spacing-4-mm-4-pole-length-28-mm-white-145203>