



**WAGO 1-CONDUCTOR MALE CONNECTOR; 4 MM<sup>2</sup>; PIN SPACING 5 MM; 12-POLE;**  
**4,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Nominal cross-section: 4 mm<sup>2</sup>;  
Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar poli: 12;  
Numar total de conexiuni: 12;  
Total number of potentials: 12;  
Wiring type: Front-entry wiring;  
Distanta intre pini: 5 mm / 0.197 inch;  
Latime: 63,6 mm / 2.504 inch;  
Inaltime: 18,3 mm / 0.72 inch;  
Adancime: 40,2 mm / 1.583 inch;  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for conductor;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,694; MJ  
Greutate: 35,2; g  
Product Group: 18 (X-COM-System);

Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918521710;  
Customs tariff number: 85366990990;  
Pret: 45,33 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-male-connector-4-mm2-pin-spacing-5-mm-12-pole-4-00-mm2-gray-145247>