



WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID AND STRANDED CONDUCTORS; FOR EX APPLICATIONS; MAX. 2.5 MM²; 2-CONDUCTOR; LIGHT GRAY HOUSING; LIGHT GRAY COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 2,50 MM²

Ratings per: IEC/EN 60664-1;
Current nominal: 24; A
Nominal voltage EN (Ex e II): 550; V
Connection technology: PUSH WIRE®;
Action type: Push-in;
Connectable conductor materials: Copper; Aluminum;
Solid conductor: 0,75 ... 2,5 mm² / 18 ... 14 AWG;
Strip length: 12 mm / 0.47 inch;
Total number of connections: 2;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Length: 9,2 mm / 0.362 inch;
Height: 13,1 mm / 0.516 inch;
Depth: 19,5 mm / 0.768 inch;
Cover Color: light gray;
Flammability class per UL94: V2;
Fire load: 0,039; MJ
Weight: 1,6; g
Surrounding air temperature (operation): 60 °C;
Continuous operating temperature: 105 °C;
Product Group: 7 (Push Wire Conn.);
Packaging: BOX;
Origin: CN;

GTIN: 4055143026420;

Customs tariff number: 85369010000;

Pret: 1,97 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-and-stranded-conductors-for-ex-applications-max-2-5-mm2-2-conductor-light-gray-housing-light-gray-cover-surrounding-air-temperature-max-600c-2-50-mm2-145596>