



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 185 MM²; LATERAL MARKER SLOTS; WITH FIXING FLANGES; POWER CAGE CLAMP; 185,00 MM²; BLUE

Voltage type 1: AC/DC;

Voltage type 2: DC;

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 12; kV

Curent nominal: 353; A

Tensiune nominala (III/3) 2: 1500; V

Tensiune nominala de supratensiune (III/3) 2: 12; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: POWER CAGE CLAMP;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 185 mm²;

Solid conductor: 50 ... 185 mm² / 1/0 AWG ... 350 kcmil;

Stranded conductor: 50 ... 185 mm² / 1/0 AWG ... 350 kcmil;

Fine-stranded conductor: 50 ... 185 mm² / 1/0 AWG ... 350 kcmil;

Fine-stranded conductor; with insulated ferrule: 50 ... 150 mm² / 1/0 AWG ... 300 kcmil;

Fine-stranded conductor; with uninsulated ferrule: 50 ... 185 mm² / 1/0 AWG ... 350 kcmil;

Strip length: 45 ... 47 mm / 1.77 ... 1.85 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 32 mm / 1.26 inch;

Inaltime de la fata: 123 mm / 4.843 inch;

Adancime: 170 mm / 6.693 inch;
Design: horizontal;
Tip montaj: Mounting flange;
Marking level: Side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Greutate: 552; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143424158;
Customs tariff number: 85369010000;
Pret: 255,35 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-185-mm2-lateral-marker-slots-with-fixing-flanges-power-cage-clamp-185-00-mm2-blue-145631>