



**WAGO 1-CONDUCTOR FEMALE PLUG; 4 MM<sup>2</sup>; 3-POLE; 4,00 MM<sup>2</sup>; GREEN-YELLOW, GRAY**

Ratings per: IEC/EN 61984;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm<sup>2</sup>;

Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 3;

Numar total de conexiuni: 3;

Total number of potentials: 3;

Wiring type: Front-entry wiring;

Latime: 15 mm / 0.591 inch;

Inaltime: 45,2 mm / 1.78 inch;

Adancime: 18,3 mm / 0.72 inch;

Module Latime: 5 mm / 0.197 inch;

Marking level: Side marking;

Tip contact (pluggable connector): Conector mama/priza;

Connector (connection type): for conductor;

Culoare: green-yellow, gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,161; MJ

Greutate: 9,6; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454271527;  
Customs tariff number: 85366990990;  
Pret: 15,35 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-female-plug-4-mm2-3-pole-4-00-mm2-green-yellow-gray-145664>