



**WAGO MODULAR TOPJOB®S CONNECTOR; MODULAR; FOR JUMPER CONTACT  
SLOT; 1-POLE; 6,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm<sup>2</sup>;

Solid conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;

Solid conductor; push-in termination: 2,5 ... 6 mm<sup>2</sup> / 14 ... 10 AWG;

Fine-stranded conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;

Fine-stranded conductor; with insulated ferrule: 1,5 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1,5 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;

Numar poli: 1;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Wiring type: Side-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 7,5 mm / 0.295 inch;

Inaltime: 46 mm / 1.811 inch;

Adancime: 23,4 mm / 0.921 inch;

Module Latime: 7,5 mm / 0.295 inch;

Marking level: Center/side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,069; MJ

Greutate: 4,3; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821263715;

Customs tariff number: 39269097900;

Pret: 12,06 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/modular-topjob-s-connector-modular-for-jumper-contact-slot-1-pole-6-00-mm2-gray-145789>