



**WAGO THT MALE HEADER; 1.0 X 1.0 MM SOLDER PIN; ANGLED; CLAMPING
COLLAR; PIN SPACING 5 MM; 3-POLE; GRAY**

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 500; V

Tensiune nominala de supratensiune (III/2): 4; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Numar poli: 3;

Total number of potentials: 3;

Numar nivele: 1;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 29,7 mm / 1.169 inch;

Inaltime de la fata: 18,3 mm / 0.72 inch;

Adancime: 22,2 mm / 0.874 inch;

Tip montaj: Mounting flange;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for PCBs;

Mismating protection: No;

Mating direction to the PCB: 0; °

PCB contact: THT;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,104; MJ

Greutate: 4,5; g

Product Group: 18 (X-COM-System);

Tip ambalare: BOX;

Tara de origine: PL;

GTIN: 4044918396585;

Customs tariff number: 85366990990;

Pret: 5,55 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-male-header-1-0-x-1-0-mm-solder-pin-angled-clamping-collar-pin-spacing-5-mm-3-pole-gray-145792>