



**WAGO BUSBAR TERMINAL BLOCK; FOR (10 X 3) MM BUSBARS; 12-POLE;
WITHOUT PUSH-BUTTONS; 4 MM²; 4,00 MM²; DARK GRAY**

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 96; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;

Solid conductor; push-in termination: 0.5 ... 4 mm² / 20 ... 12 AWG;

Stranded conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;

Fine-stranded conductor: 0.5 ... 4 mm² / 20 ... 12 AWG;

Strip length: 11 mm / 0.43 inch;

Numar poli: 12;

Numar total de conexiuni: 12;

Total number of potentials: 12;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 75 mm / 2.953 inch;

Inaltime: 30 mm / 1.181 inch;

Adancime: 27.5 mm / 1.083 inch;

Culoare: dark gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,823; MJ

Greutate: 35,7; g

Product Group: 12 (Matrix Patch Board);

Tip ambalare: BOX;

Tara de origine: PL;
GTIN: 4044918253277;
Customs tariff number: 85369010000;
Pret: 32,43 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/busbar-terminal-block-for-10-x-3-mm-busbars-12-pole-without-push-buttons-4-mm2-4-00-mm2-dark-gray-145796>