



**WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID AND STRANDED CONDUCTORS; FOR EX APPLICATIONS; MAX. 2.5 MM<sup>2</sup>; 4-CONDUCTOR; LIGHT GRAY HOUSING; LIGHT GRAY COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 2,50 MM<sup>2</sup>**

Ratings per: IEC/EN 60664-1;  
Current nominal: 24; A  
Nominal voltage EN (Ex e II): 550; V  
Connection technology: PUSH WIRE®;  
Action tip: Push-in;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0,75 ... 2,5 mm<sup>2</sup> / 18 ... 14 AWG;  
Strip length: 12 mm / 0.47 inch;  
Total number of connections: 4;  
Total number of potentials: 1;  
Wiring type: Side-entry wiring;  
Length: 13 mm / 0.512 inch;  
Height: 13,1 mm / 0.516 inch;  
Depth: 19,5 mm / 0.768 inch;  
Cover Color: light gray;  
Flammability class per UL94: V2;  
Fire load: 0,053; MJ  
Weight: 2,4; g  
Surrounding air temperature (operation): 60 °C;  
Continuous operating temperature: 105 °C;  
Product Group: 7 (Push Wire Conn.);  
Packaging: BOX;  
Origin: CN;

GTIN: 4055143026512;  
Customs tariff number: 85369010000;  
Pret: 2,27 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/push-wire-connector-for-connection-boxes-for-solid-and-stranded-conductors-for-ex-applications-max-2-5-mm2-4-conductor-light-gray-housing-light-gray-cover-surrounding-air-temperature-max-600c-2-50-mm2-145986>