



WAGO BOARD-TO-BOARD LINK; PIN SPACING 6.5 MM; LENGTH: 17.6 MM

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tensiune nominala (II/2): 630; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 9; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Numar tipuri de conexiuni: 1;
Adancime: 17,6 mm / 0.693 inch;
Length: 17,6; mm
Length: 17,6; mm
Diameter: 1; mm
Diameter: 1; mm
Mating cycles (max.): 10;
Number of mating cycles: max. 10 connections/disconnections;
Suitable: for SMD PCB Terminal Blocks; 2065 Series;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Contact material: Copper alloy;
Contact plating: tin-plated;
Greutate: 0,1; g
Temperatura lucru: -60 ... +120 °C;
Tip ambalare: BOX;
Tara de origine: DE;

GTIN: 4055143862738;

Customs tariff number: 85369010000;

Pret: 0,54 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/board-to-board-link-pin-spacing-6-5-mm-length-17-6-mm-146030>