



WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID AND STRANDED CONDUCTORS; FOR EX APPLICATIONS; MAX. 2.5 MM²; 3-CONDUCTOR; LIGHT GRAY HOUSING; LIGHT GRAY COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 6,00 MM²

Ratings per: IEC/EN 60664-1;
Current nominal: 42; A
Nominal voltage EN (Ex e II): 550; V
Technology connection: PUSH WIRE®;
Tip action: Push-in;
Connectable conductor materials: Copper; Aluminum;
Solid conductor: 2,5 ... 6 mm² / 14 ... 10 AWG;
Strip length: 12 ... 15 mm / 0.47 ... 0.59 inch;
Total number of connections: 3;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Length: 25,6 mm / 1.008 inch;
Height: 14,2 mm / 0.559 inch;
Depth: 20,1 mm / 0.791 inch;
Cover Color: light gray;
Flammability class per UL94: V2;
Fire load: 0,113; MJ
Weight: 5,8; g
Surrounding air temperature (operation): 60 °C;
Continuous operating temperature: 105 °C;
Product Group: 7 (Push Wire Conn.);
Packaging: BOX;
Origin: CN;

GTIN: 4055143287593;
Customs tariff number: 85369010000;
Pret: 3,52 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/push-wire-connector-for-connection-boxes-for-solid-and-stranded-conductors-for-ex-applications-max-2-5-mm2-3-conductor-light-gray-housing-light-gray-cover-surrounding-air-temperature-max-600c-6-00-mm2-146122>