



**WAGO BOARD-TO-BOARD LINK; PIN SPACING 6 MM; 1-POLE; LENGTH: 34 MM;**  
**WHITE**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Tensiune nominala (III/2): 320; V  
Tensiune nominala de supratensiune (III/2): 4; kV  
Tensiune nominala (II/2): 630; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 9; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Numar poli: 1;  
Total number of potentials: 1;  
Numar tipuri de conexiuni: 1;  
Distanta intre pini: 6 mm / 0.236 inch;  
Latime: 5,7 mm / 0.224 inch;  
Inaltime: 2,5 mm / 0.098 inch;  
Adancime: 34 mm / 1.339 inch;  
Mating cycles (max.): 10;  
Number of mating cycles: max. 10 connections/disconnections;  
Suitable: for SMD PCB Terminal Blocks; 2061 Series;  
Culoare: white;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Contact material: Copper alloy;  
Contact plating: silver-plated;

Greutate: 0,3; g

Temperatura lucru: -60 ... +105 °C;

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4055143656849;

Customs tariff number: 85369010000;

Pret: 1,43 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/board-to-board-link-pin-spacing-6-mm-1-pole-length-34-mm-white-146262>