



**WAGO MULTILEVEL INSTALLATION TERMINAL BLOCK; 4 MM²; CARRIER
TERMINAL BLOCK WITHOUT KNIFE; P2/P1/PE; BLACK UPPER DECK; BROWN
MIDDLE DECK; GREEN-YELLOW LOWER DECK; PUSH-IN CAGE CLAMP®; 2,50
MM²; GRAY**

Ratings (note): Potential – ground;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 10; A

Ratings (note) 2: Potential – potential;

Tensiune nominala (III/3) 2: 400; V

Tensiune nominala de supratensiune (III/3) 2: 6; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 250; V

Curent nominal UL (Use Group B): 6,3; A

Tensiune nominala UL (Use Group C): 250; V

Curent nominal UL (Use Group C): 6,3; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group C): 300; V

Curent nominal CSA (Use Group C): 20; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;
Numar total de conexiuni: 5;
Total number of potentials: 3;
Numar nivele: 3;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Latime: 5,2 mm / 0.205 inch;
Inaltime from upper-edge of DIN-rail: 45,2 mm / 1.78 inch;
Adancime: 110 mm / 4.331 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Potential marking: P2/P1/PE;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,309; MJ
Greutate: 19,9; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821464525;
Customs tariff number: 85369010000;
Pret: 23,17 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/multilevel-installation-terminal-block-4-mm2-carrier-terminal-block-without-knife-p2-p1-pe-black-upper-deck-brown-middle-deck-green-yellow-lower-deck-push-in-cage-clamp-2-50-mm2-gray-146333>