



**WAGO 1-CONDUCTOR FEMALE PLUG; STRAIN RELIEF PLATE; 1-POLE; 2,50 MM²;
GREEN-YELLOW**

Ratings per: IEC/EN 61984;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2.5 mm²;

Solid conductor: 0.25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0.75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0.25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2.5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2.5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar poli: 1;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 5.2 mm / 0.205 inch;

Inaltime: 56.5 mm / 2.224 inch;

Adancime: 27.2 mm / 1.071 inch;

Module Latime: 5.2 mm / 0.205 inch;

Marking level: Side marking;

Tip contact (pluggable connector): Conector mama/priza;

Connector (connection type): for conductors;

Culoare: green-yellow;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,076; MJ
Greutate: 3,9; g
Product Group: 18 (X-COM-System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821091165;
Customs tariff number: 85366990990;
Pret: 12,54 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-female-plug-strain-relief-plate-1-pole-2-50-mm2-green-yellow-146407>