



**WAGO 1-CONDUCTOR FEMALE PLUG; STRAIN RELIEF PLATE; 1.5 MM<sup>2</sup>; 4-POLE;**  
**1,50 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 61984;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 13,5; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 15; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 1 mm<sup>2</sup>;

Solid conductor: 0.14 ... 1.5 mm<sup>2</sup> / 24 ... 16 AWG;

Solid conductor; push-in termination: 0.5 ... 1.5 mm<sup>2</sup> / 20 ... 16 AWG;

Fine-stranded conductor: 0.14 ... 1.5 mm<sup>2</sup> / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 0.75 mm<sup>2</sup> / 20 ... 18 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.5 ... 0.75 mm<sup>2</sup> / 20 ... 18 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar poli: 4;

Numar total de conexiuni: 4;

Total number of potentials: 4;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 14.7 mm / 0.579 inch;

Inaltime: 59 mm / 2.323 inch;

Adancime: 27.2 mm / 1.071 inch;

Module Latime: 3.5 mm / 0.138 inch;

Marking level: Side marking;

Tip contact (pluggable connector): Conector mama/priza;

Connector (connection type): for conductors;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,201; MJ

Greutate: 10,4; g

Product Group: 18 (X-COM-System);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821092551;

Customs tariff number: 85366990990;

Pret: 24,25 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-female-plug-strain-relief-plate-1-5-mm2-4-pole-1-50-mm2-gray-146420>