



**WAGO 2-CONDUCTOR SHIELD TERMINAL BLOCK; 16 MM²; CENTER MARKING;
FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 16,00 MM²; WHITE**

Ratings per: IEC/EN 60947-7-2;
Tensiune nominala (III/3): 800; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 76; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,2 ... 16 mm² / 24 ... 6 AWG;
Fine-stranded conductor: 0,2 ... 16 mm² / 24 ... 6 AWG;
Strip length: 16 ... 17 mm / 0.63 ... 0.67 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 12 mm / 0.472 inch;
Inaltime from upper-edge of DIN-rail: 37,5 mm / 1.476 inch;
Adancime: 94,5 mm / 3.72 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center marking;
Culoare: white;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,502; MJ
Greutate: 46,6; g
Tip ambalare: BOX;
Tara de origine: DE;

GTIN: 4045454084578;

Customs tariff number: 85369010000;

Pret: 37,03 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-shield-terminal-block-16-mm2-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-16-00-mm2-white-146544>