



WAGO BOARD-TO-BOARD LINK; PIN SPACING 3 MM; 2-POLE; LENGTH: 20.5 MM;
WHITE

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 63; V
Tensiune nominala de supratensiune (III/3): 2,5; kV
Tensiune nominala (III/2): 160; V
Tensiune nominala de supratensiune (III/2): 2,5; kV
Tensiune nominala (II/2): 320; V
Tensiune nominala de supratensiune (II/2): 2,5; kV
Curent nominal: 3; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Numar poli: 2;
Total number of potentials: 2;
Numar tipuri de conexiuni: 1;
Distanta intre pini: 3 mm / 0.118 inch;
Latime: 5,7 mm / 0.224 inch;
Inaltime: 2,5 mm / 0.098 inch;
Adancime: 20,5 mm / 0.807 inch;
Mating cycles (max.): 10;
Number of mating cycles: max. 10 connections/disconnections;
Suitable: for SMD PCB Terminal Blocks; 2059 Series;
Culoare: white;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Contact material: Copper alloy;
Contact plating: silver-plated;

Greutate: 0,2; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4055143610070;
Customs tariff number: 85369010000;
Pret: 2,21 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/board-to-board-link-pin-spacing-3-mm-2-pole-length-20-5-mm-white-146623>