



**WAGO 3-CONDUCTOR SHIELD TERMINAL BLOCK; 2.5 MM<sup>2</sup>; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 2,50 MM<sup>2</sup>; WHITE**

Ratings per: IEC/EN 60947-7-2;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 20; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 20; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm<sup>2</sup>;

Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 3;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 5,2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 38,9 mm / 1.531 inch;

Adancime: 52,6 mm / 2.071 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: white;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,107; MJ  
Greutate: 8,6; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4045454752569;  
Customs tariff number: 85369010000;  
Pret: 21,20 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-shield-terminal-block-2-5-mm2-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-2-50-mm2-white-146725>