



**WAGO START MODULE FOR 2-CONDUCTOR FEMALE CONNECTOR; 1.5 MM<sup>2</sup>; 1-  
POLE; 1,50 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 61984;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 15; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 1 mm<sup>2</sup>;

Solid conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;

Solid conductor; push-in termination: 0,5 ... 1,5 mm<sup>2</sup> / 20 ... 16 AWG;

Fine-stranded conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar poli: 1;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 4,2 mm / 0.165 inch;

Inaltime: 40,5 mm / 1.594 inch;

Adancime: 25 mm / 0.984 inch;  
Marking level: Side marking;  
Tip contact (pluggable connector): Conector mama/priza;  
Connector (connection type): for conductor;  
Culoare: green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,06; MJ  
Greutate: 3,2; g  
Product Group: 18 (X-COM-System);  
Tip ambalare: bag;  
Tara de origine: DE;  
GTIN: 4045454861339;  
Customs tariff number: 85366990990;  
Pret: 12,60 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/start-module-for-2-conductor-female-connector-1-5-mm2-1-pole-1-50-mm2-green-yellow-147094>