



**WAGO 1-CONDUCTOR MALE CONNECTOR; 4 MM<sup>2</sup>; PIN SPACING 5 MM; 11-POLE;**  
**4,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm<sup>2</sup>;

Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 11;

Numar total de conexiuni: 11;

Total number of potentials: 11;

Wiring type: Front-entry wiring;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 58,6 mm / 2.307 inch;

Inaltime: 18,3 mm / 0.72 inch;

Adancime: 40,2 mm / 1.583 inch;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for conductor;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,633; MJ

Greutate: 32,1; g

Product Group: 18 (X-COM-System);

Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918521659;  
Customs tariff number: 85366990990;  
Pret: 41,68 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-male-connector-4-mm2-pin-spacing-5-mm-11-pole-4-00-mm2-gray-147180>