



WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR SOLID AND STRANDED CONDUCTORS; MAX. 2.5 MM²; 6-CONDUCTOR; TRANSPARENT HOUSING; GREEN COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 2,50 MM²

Ratings per: IEC/EN 60664-1;
Tesiune nominala (II/2): 400; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 24; A
Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Connectable conductor materials: Copper; Aluminum;
Solid conductor: 0,75 ... 2,5 mm² / 18 ... 12 AWG;
Stranded conductor: 1,5 ... 2,5 mm² / 16 ... 12 AWG;
Strip length: 12 mm / 0.47 inch;
Numar total de conexiuni: 6;
Total number of potentials: 1;
Wiring type: Side-entry wiring;
Latime: 18,8 mm / 0.74 inch;
Inaltime: 13,1 mm / 0.516 inch;
Adancime: 19,5 mm / 0.768 inch;
Cover Culoare: green;
Flammability class per UL94: V2;
Greutate: 3,5; g
Surrounding air temperature (operation): 60 °C;
Tip ambalare: BOX;
Tara de origine: CN;

GTIN: 4055143237550;

Customs tariff number: 85369010000;

Pret: 1,49 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-and-stranded-conductors-max-2-5-mm2-6-conductor-transparent-housing-green-cover-surrounding-air-temperature-max-600c-2-50-mm2-147267>