



WAGO BOARD-TO-BOARD LINK; PIN SPACING 6 MM; 1-POLE; LENGTH: 30 MM;
WHITE

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tensiune nominala (II/2): 630; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 9; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Numar poli: 1;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Distanta intre pini: 6 mm / 0.236 inch;
Latime: 5,7 mm / 0.224 inch;
Inaltime: 2,5 mm / 0.098 inch;
Adancime: 30 mm / 1.181 inch;
Mating cycles (max.): 10;
Number of mating cycles: max. 10 connections/disconnections;
Suitable: for SMD PCB Terminal Blocks; 2061 Series;
Culoare: white;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Contact material: Copper alloy;
Contact plating: silver-plated;

Greutate: 0,3; g

Temperatura lucru: -60 ... +105 °C;

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4055143656856;

Customs tariff number: 85369010000;

Pret: 1,37 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/board-to-board-link-pin-spacing-6-mm-1-pole-length-30-mm-white-147281>