



**WAGO MALE CONNECTOR FOR RAIL-MOUNT TERMINAL BLOCKS; 1.2 X 1.2 MM PINS; STRAIGHT; PIN SPACING 5 MM; 20-POLE; GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 15; A

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 15; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Numar poli: 20;

Total number of potentials: 20;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 103,2 mm / 4.063 inch;

Inaltime: 25,9 mm / 1.02 inch;  
Inaltime de la fata: 12 mm / 0.472 inch;  
Adancime: 8,4 mm / 0.331 inch;  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for front-entry wiring terminal block;  
Mismatching protection: No;  
Culoare: gray;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,15; MJ  
Greutate: 11,2; g  
Temperatura lucru: -60 ... +100 °C;  
Product Group: 3 (Multi Conn. System);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918905510;  
Customs tariff number: 85366990990;  
Pret: 39,53 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/male-connector-for-rail-mount-terminal-blocks-1-2-x-1-2-mm-pins-straight-pin-spacing-5-mm-20-pole-gray-147537>