



**WAGO MODULAR TOPJOB®S CONNECTOR; MODULAR; FOR JUMPER CONTACT
SLOT; 3-POLE; 1,00 MM²; GRAY**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 13,5; A

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tensiune nominala CSA (Use Group C): 300; V

Curent nominal CSA (Use Group C): 10; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Nominal cross-section: 1 mm²;

Solid conductor: 0.14 ... 1.5 mm² / 24 ... 16 AWG;

Solid conductor; push-in termination: 0.5 ... 1.5 mm² / 20 ... 16 AWG;

Fine-stranded conductor: 0.14 ... 1.5 mm² / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 0.75 mm² / 20 ... 18 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.5 ... 0.75 mm² / 20 ... 18 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar poli: 3;

Numar total de conexiuni: 3;

Total number of potentials: 3;

Wiring type: Side-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 12 mm / 0.472 inch;

Module Latime: 3.5 mm / 0.138 inch;

Marking level: Center/side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Greutate: 6,1; g

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4055143394697;

Customs tariff number: 85366990990;

Pret: 32,43 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/modular-topjob-s-connector-modular-for-jumper-contact-slot-3-pole-1-00-mm2-gray-148094>