



**WAGO 1-CONDUCTOR FEMALE PLUG; ANGLED; 100% PROTECTED AGAINST
MISMATING; SNAP-IN MOUNTING FEET; 2.5 MM²; PIN SPACING 5 MM; 13-POLE;
2,50 MM²; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 12; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 15; A

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 15; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm²;
Strip length: 7 ... 8 mm / 0.28 ... 0.31 inch;
Numar poli: 13;
Numar total de conexiuni: 13;
Total number of potentials: 13;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Conductor entry direction to mating direction: 90; °
Distanta intre pini: 5 mm / 0.197 inch;
Latime: 66.5 mm / 2.618 inch;
Inaltime: 17.6 mm / 0.693 inch;
Inaltime de la fata: 13.1 mm / 0.516 inch;
Adancime: 27.25 mm / 1.073 inch;
Housing sheet thickness: 0.6 ... 1.2 mm / 0.024 ... 0.047 inch;
Design: angled; mountable;
Tip montaj: Snap-in mounting foot;
Tip montaj: Feed-through mounting; Panel mounting;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductors;
Mismating protection: Yes;
Culoare: light gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy;
Contact plating: tin-plated;
Fire load: 0,381; MJ
Greutate: 19,4; g
Temperatura lucru: -60 ... +85 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4017332760881;
Customs tariff number: 85366990990;
Pret: 50,52 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-female-plug-angled-100-protected-against-mismating-snap-in-mounting-feet-2-5-mm2-pin-spacing-5-mm-13-pole-2-50-mm2-light-gray-149535>