



**WAGO 1-CONDUCTOR POWER DISTRIBUTION DISCONNECT TERMINAL BLOCK;
16 MM²; CAGE CLAMP®; 16,00 MM²; GRAY**

Tensiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 68; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Open Tool Slot;
Connectable conductor materials: Copper;
Solid conductor: 0,2 ... 16 mm² / 24 ... 6 AWG;
Fine-stranded conductor: 0,2 ... 16 mm² / 24 ... 6 AWG;
Strip length: 16 ... 17 mm / 0.63 ... 0.67 inch;
Numar total de conexiuni: 1;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 12 mm / 0.472 inch;
Inaltime from upper-edge of DIN-rail: 43,5 mm / 1.713 inch;
Adancime: 88,5 mm / 3.484 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Marking level: Center marking;
Culoare: gray;
Greutate: 43,5; g
Product Group: 17 (TOP JOB installation terminal blocks);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4044918691475;

Customs tariff number: 85365080900;
Pret: 23,17 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-power-distribution-disconnect-terminal-block-16-mm2-cage-clamp-16-00-mm2-gray-150323>