



**WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP; 4-POLE; PE-N-L1-L2;  
WITH GROUND CONTACT; 4 MM<sup>2</sup>; 4,00 MM<sup>2</sup>; BLACK**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool; Push-button;

Connectable conductor materials: Copper;

Solid conductor: 0.5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;

Solid conductor; push-in termination: 0.75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Stranded conductor: 0.5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;

Fine-stranded conductor: 0.5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 2.5 mm<sup>2</sup> / 20 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.75 mm<sup>2</sup> / 18 AWG;

Strip length: 10 ... 11 mm / 0.39 ... 0.43 inch;

Numar poli: 4;

Numar total de conexiuni: 16;

Total number of potentials: 4;

Wiring type: Side-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Distanta intre pini: 12 mm / 0.472 inch;

Latime: 48 mm / 1.89 inch;

Inaltime de la fata: 22.3 mm / 0.878 inch;

Adancime: 35 mm / 1.378 inch;

Tip montaj: Snap-in mounting foot;

Marking: PE-N-L1-L2;

Culoare: black;  
Fire load: 0,505; MJ  
Greutate: 28,4; g  
Tip ambalare: bag;  
Tara de origine: DE;  
GTIN: 4044918511049;  
Customs tariff number: 85369010000;  
Pret: 18,63 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-chassis-mount-terminal-strip-4-pole-pe-n-11-12-with-ground-contact-4-mm2-4-00-mm2-black-150414>