



**WAGO 8-LEVEL TERMINAL BLOCK FOR MATRIX PATCHING; FOR 35 X 15
MOUNTING RAIL; 1,50 MM²; GRAY**

Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 10; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;
Fine-stranded conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;
Strip length: 8 ... 10 mm / 0.31 ... 0.39 inch;
Numar total de conexiuni: 32;
Total number of potentials: 8;
Numar nivele: 8;
Wiring type: Front-entry wiring;
Latime: 7,62 mm / 0.3 inch;
Inaltime from upper-edge of DIN-rail: 76 mm / 2.992 inch;
Adancime: 226 mm / 8.898 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking: h-g-f-e-d-c-b-a--a-b-c-d-e-f-g-h;
Marking level: Center marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 1,187; MJ
Greutate: 74,6; g
Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4045454187750;
Customs tariff number: 85369010000;
Pret: 104,27 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/8-level-terminal-block-for-matrix-patching-for-35-x-15-mounting-rail-1-50-mm2-gray-150422>