



WAGO 8-LEVEL TERMINAL BLOCK FOR MATRIX PATCHING; FOR 35 X 15 MOUNTING RAIL; 1,50 MM²; GRAY

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 10; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;

Fine-stranded conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;

Strip length: 8 ... 10 mm / 0.31 ... 0.39 inch;

Numar total de conexiuni: 32;

Total number of potentials: 8;

Numar nivele: 8;

Wiring type: Front-entry wiring;

Latime: 7,62 mm / 0.3 inch;

Inaltime from upper-edge of DIN-rail: 76 mm / 2.992 inch;

Adancime: 226 mm / 8.898 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking: h-g-f-e-d-c-b-a--a-b-c-d-e-f-g-h;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 1,187; MJ

Greutate: 74,6; g

Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4045454187750;
Customs tariff number: 85369010000;
Pret: 104,27 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/8-level-terminal-block-for-matrix-patching-for-35-x-15-mounting-rail-1-50-mm2-gray-150422>