



**WAGO 2-CONDUCTOR DISCONNECT/TEST TERMINAL BLOCK; WITH PIVOTING KNIFE DISCONNECT; WITH TEST OPTION; ORANGE DISCONNECT LINK; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 6 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 6,00 MM<sup>2</sup>; BLUE**

Voltage type 1: AC/DC;

Voltage type 2: DC;

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 12; kV

Curent nominal: 30; A

Tensiune nominala (III/3) 2: 1500; V

Tensiune nominala de supratensiune (III/3) 2: 12; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 30; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 30; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 30; A

Tensiune nominala CSA (Use Group C): 1000; V

Curent nominal CSA (Use Group C): 30; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm<sup>2</sup>;

Solid conductor: 0.5 ... 10 mm<sup>2</sup> / 20 ... 8 AWG;

Solid conductor; push-in termination: 2.5 ... 10 mm<sup>2</sup> / 14 ... 8 AWG;

Fine-stranded conductor: 0.5 ... 10 mm<sup>2</sup> / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2.5 ... 6 mm<sup>2</sup> / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2.5 ... 6 mm<sup>2</sup> / 16 ... 10 AWG;  
Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;  
Number of jumper slots: 2;  
Latime: 15 mm / 0.591 inch;  
Inaltime from upper-edge of DIN-rail: 33 mm / 1.299 inch;  
Adancime: 106.9 mm / 4.209 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: blue;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,673; MJ  
Greutate: 31,4; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821372516;  
Customs tariff number: 85365080900;  
Pret: 30,70 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-disconnect-test-terminal-block-with-pivoting-knife-disconnect-with-test-option-orange-disconnect-link-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-push-in-cage-clamp-6-00-mm2-blue-150481>